
Heavy Duty LatexExamination Gloves



PRODUCT INFORMATION				
MATERIAL	Latex*			
COLOR	Dark blue			
TYPE	Ambidextrous, non-sterile, single-use			
INTERIOR	Powder-free			
EXTERIOR	Textured			
COUNTRY OF ORIGIN	Malaysia			
STORAGE	Store in original packaging in a cool, dry and well ventilated area, away from dust, direct sunlight, moisture, x-ray and excessive heat above 100°F (37°C)			
RESTRICTIONS ON USE	Do not use for handling organic solvents as glove degradation can occur			

PHYSICAL PROPERTIES				
AQL	1.5			
GLOVE WEIGHT	15.5grams (medium)			
GLOVE THICKNESS	13mil			
GLOVE LENGTH	12"			
	BEFORE AGING	AFTER AGING		
TENSILE STRENGTH (MPA)	min. 18	min. 14		
ULTIMATE ELONGATION	min. 650%	min. 500%		







QUALITY STANDARDS		
FDA STATUS	(21 CFR 177) compliant for food handling (510k) cleared for medical use	
AUDIT STANDARDS	Manufactured in an ISO 9001:2015 and an ISO 13485:2016 facility Manufactured in a Certified WRAP Facility	
TEST STANDARDS	ASTM D6978 - Chemotherapy drug Permeation ASTM F1671 - Viral penetration tested EN ISO 374-1:2016/Type B EN ISO 374-5: 3016 Resistance to Bacteria, Fungi and Virus EN 16523-1:2015 Resistance to Chemical Permeation EN374-2 Resistance to Microbial Penetration NFPA 1999 certified	

PACKAGING & ORDERING INFORMATION					
CODE	SIZE	PURCHASE UNIT	CASE DIMENSIONS (LxWxH)	CASE WEIGHTS	CUBIC FEET
1130202	S				
1130302	М				
1130402	L	1 carton of 500 gloves (50/box x 10)	17.7 × 11.1 × 10.6"	18.4lbs	1.05ft³
1130502	XL	(33, 23, 7, 10)			
1130602	2XL				

RESISTANCE OF GLOVES TO PERMEATION BY CHEMICALS							
CHEMICAL		EN ISO 374-1:2016 PERFORMANCE LEVEL			EN 374-4:2013 MEAN DEGRADATION / %		
Diethylamine (G)		0		20.4			
Ethanol	0			-17.6			
Isopropanol 70%	1			-10.7			
Diethyl Ether	0			3.1			
Sodium Hydroxide 40% (K)	6			-40.0			
Sulphuric Acid 96% (L)	2			27.8			
Ammonium Hydroxide 25% (O)	1			-215.7			
Nitric Acid 65% (M)	4			-0.9			
Acetic Acid 50%	2 -78.8			}			
Chlorhexidine Digluconate 4%	6 7.0						
Saturated Benzalkoium Chloride	6		25.6				
Formaldehyde 37% (T)	6		-97.8				
Glutaraldehyde 50%	6			-36.4			
Hydrogen Peroxide 30% (P)	5			22.8			
EN ISO 374-1:2016 - permeation levels are based on breakthrough times as follows:							
Performance Level:	1	2	3	4	5	6	
Minimum breakthrough time (Min):	>10	>30	>60	>120	>240	>480	

Safety gloves to protect against chemicals are classified according to their permeation time (time taken for the chemical to penetrate the glove) and number of chemicals tested:

- Type A at least 30min each for at least 6 test chemicals
- Type B at least 30min each for at least 3 test chemicals
- Type C at least 10min each for at least 1 test chemicals

EN 374-4:2013 - Degradation results indicate the change in puncture resistance of the gloves after exposure to the challenge chemical **EN ISO 374-5:2016 -** Resistance to Bacteria and Fungi = Pass, Resistance to Virus = Pass

CHEMOTHERAPY DRUGS PERMEATION TEST (ASTM D6978-05 (2013))					
CHEMICAL	MIN BREAKTHROUGH DETECTION TIME (mins)	OBSERVATIONS			
Carmustine (BCNU) (3.3 mg/mL)	15.4	Moderate swelling & no degradation			
Cisplatin (1.0 mg/mL)	> 240	Slight swelling & no degradation			
Cyclophosphamide (Cytoxan) (20.0 mg/mL)	> 240	Slight swelling & no degradation			
Cytarabine (100 mg/mL)	> 240	Slight swelling & no degradation			
Dacarbazine (DTIC) (10.0 mg/mL)	> 240	Slight swelling & no degradation			
Doxorubicin Hydrochloride (2.0 mg/mL)	> 240	Slight swelling & no degradation			
Etoposide (20.0 mg/mL)	> 240	Slight swelling & no degradation			
Fluorouracil (50.0 mg/mL)	> 240	Slight swelling & no degradation			
Ifosfamide (50.0 mg/mL)	> 240	Slight swelling & no degradation			
Methotrexate (25 mg/mL)	> 240	Slight swelling & no degradation			
Mitomycin C (0.5 mg/mL)	> 240	Slight swelling & no degradation			
Mitoxantrone (2.0 mg/mL)	> 240	Slight swelling & no degradation			
Paclitaxel (Taxol) (6.0 mg/ml)	> 240	Moderate swelling & no degradation			
Thiotepa (10.0 mg/mL)	30.6	Slight swelling & no degradation			
Vincristine Sulfate (1.0 mg/mL)	> 240	Slight swelling & no degradation			



Contact us today to receive samples or for more information on this product.



sales@eagleprotect.com eagleprotect.com 1 800 384 3905 **Head Office**

3079 Harrison Avenue #21 South Lake Tahoe California 96150



